

Package: glmMisrep (via r-universe)

September 16, 2024

Type Package

Title Generalized Linear Models Adjusting for Misrepresentation

Version 0.1.1

Depends R (>= 3.5.0)

Description Fit Generalized Linear Models to continuous and count outcomes, as well as estimate the prevalence of misrepresentation of an important binary predictor. Misrepresentation typically arises when there is an incentive for the binary factor to be misclassified in one direction (e.g., in insurance settings where policy holders may purposely deny a risk status in order to lower the insurance premium). This is accomplished by treating a subset of the response variable as resulting from a mixture distribution. Model parameters are estimated via the Expectation Maximization algorithm and standard errors of the estimates are obtained from closed forms of the Observed Fisher Information. For an introduction to the models and the misrepresentation framework, see Xia et. al., (2023)

<<https://variancejournal.org/article/73151-maximum-likelihood-approaches-to-misrepresentation-models-in-glm-ratemaking-model-comparison>

License GPL (>= 2)

Encoding UTF-8

LazyData true

Imports MASS, poisson.glm.mix, stats

NeedsCompilation no

Author Patrick Rafael [cre, aut], Xia Michelle [aut], Rexford Akakpo [aut]

Maintainer Patrick Rafael <pbr2608@vt.edu>

Date/Publication 2024-04-18 17:43:06 UTC

Repository <https://pleaseontdothat.r-universe.dev>

RemoteUrl <https://github.com/cran/glmMisrep>

RemoteRef HEAD

RemoteSha b8542e679ed56a5131833af80ada92691ad8bad

Contents

gammaRegMisrepEM	2
LnRegMisrepEM	7
MEPS14	12
nbRegMisrepEM	16
NormRegMisrepEM	21
poisRegMisrepEM	26
predict.misrepEM	31
summary.misrepEM	32
Index	35

gammaRegMisrepEM *Fit a Gamma Misrepresentation Model using EM Algorithm*

Description

gammaRegMisrepEM is used to fit a Gamma regression model, adjusting for misrepresentation on a binary predictor. The function uses the Expectation Maximization algorithm and allows multiple additional correctly measured independent variables in the Gamma regression with a log-link function that is typically used in insurance claims modeling. Standard errors of model estimates are obtained from closed form expressions of the Observed Fisher Information.

Usage

```
gammaRegMisrepEM(formula, v_star, data, lambda = c(0.6, 0.4),
                  epsilon = 1e-08, maxit = 10000,
                  maxrestarts = 20, verb = FALSE)
```

Arguments

formula	an object of class " formula " (or one that can be coerced to that class): a symbolic description of the model to be fitted. The details of model specification are given under 'Details'.
v_star	a character specifying the name of the binary predictor that is suspected of being misrepresented.
data	a dataframe containing the variables in the model.
lambda	initial mixing proportions used to start the EM algorithm. A numeric vector of length two, with the second element being the prevalence of misrepresentation.
epsilon	tolerance for convergence. Convergence is reached when the log-likelihood increases by less than epsilon.
maxit	the maximum number of iterations the EM routine will run for.
maxrestarts	how many times the EM routine will attempt to converge. When convergence is not achieved, the EM routine restarts with new randomly selected mixing proportions.

verb	logical. If TRUE, the difference in new .vs. old log-likelihood and the current log-likelihood is printed to the console after every iteration. If TRUE, the user will also be notified if the EM algorithm must restart with new mixing proportions.
------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Details

Models for `gammaRegMisrepEM` are specified symbolically. Like the `lm` and `glm` functions, the model has the form `response ~ terms`, where `response` is the numeric response vector and `terms` is a series of terms which specifies a linear predictor for `response`.

Currently, formula specification can accommodate the following expressions:

- transformations of the response: `log(y) ~ x`
- polynomial terms: `y ~ x + I(x^2)`
- interactions: `y ~ x*z`

Including an offset term (e.g. `y ~ x + offset()`) is currently not supported.

Value

`gammaRegMisrepEM` returns an object of `class "misrepEM"`.

The function `summary` is used to obtain and print a summary of the results.

An object of class "`misrepEM`" is a list containing the following 14 elements:

<code>y</code>	the response used.
<code>lambda</code>	numeric. The estimated prevalence of misrepresentation.
<code>params</code>	a numeric vector containing the estimated parameters.
<code>loglik</code>	the final maximized log-likelihood.
<code>posterior</code>	a numeric vector. The posterior probability that the <i>i-th</i> observation is not misrepresented for observations where the suspected misrepresented variable is zero, based on the last iteration of the EM algorithm. The values are not meaningful for observations where the suspected misrepresented variable is one.
<code>all.loglik</code>	a numeric vector containing the log-likelihood at every iteration.
<code>cov.estimates</code>	the inverse of the observed fisher information matrix evaluated at the maximum likelihood estimates.
<code>std.error</code>	a numeric vector containing the standard errors of regression coefficients.
<code>t.values</code>	a numeric vector containing the standardized regression coefficients.
<code>p.values</code>	a numeric vector containing the <i>p</i> -values of the regression coefficients.
<code>ICs</code>	a numeric vector of length three containing the AIC, AICc, and BIC.
<code>ft</code>	a character containing the name of the function.
<code>formula</code>	an object of class <code>formula</code> indicating the model that was fit.
<code>v_star_name</code>	a character containing the name of the binary predictor suspected of misrepresentation.

References

- Xia, Michelle, Rexford Akakpo, and Matthew Albaugh. "Maximum Likelihood Approaches to Misrepresentation Models in GLM ratemaking: Model Comparisons." *Variance* 16.1 (2023).
- Akakpo, R. M., Xia, M., & Polansky, A. M. (2019). Frequentist inference in insurance ratemaking models adjusting for misrepresentation. *ASTIN Bulletin: The Journal of the IAA*, 49(1), 117-146.
- Xia, M., Hua, L., & Vadnais, G. (2018). Embedded predictive analysis of misrepresentation risk in GLM ratemaking models. *Variance*, 12(1), 39-58.

Examples

```

set.seed(314159)

# Simulate data
n <- 1000
p0 <- 0.25

X1 <- rbinom(n, 1, 0.4)
X2 <- sample(x = c("a", "b", "c"), size = n, replace = TRUE)
X3 <- rnorm(n, 0, 1)

theta0 <- 0.3
V <- rbinom(n, 1, theta0)
V_star <- V
V_star[V==1] <- rbinom(sum(V==1), 1, 1-p0)

a0 <- 1
a1 <- 2
a2 <- 0
a3 <- -1
a4 <- 4
a5 <- 2

mu <- rep(0, n)

for(i in 1:n){

  mu[i] <- exp(a0 + a1*X1 + a4*X3 + a5*V )[i]

  if(X2[i] == "a" || X2[i] == "b"){

    mu[i] <- mu[i]*exp(a2)

  }else{
    mu[i] <- mu[i]*exp(a3)
  }

}

phi <- 0.2

```

```

alpha0 <- 1/phi
beta <- 1/mu/phi
Y <- rgamma(n, alpha0, beta)

data <- data.frame(Y = Y, X1 = X1, X2 = X2, X3 = X3, V_star = V_star)

# "a" is the reference
data$X2 <- as.factor(data$X2)

# Model with main effects:
gamma_mod <- gammaRegMisrepEM(formula = Y ~ X1 + X2 + X3 + V_star,
                                v_star = "V_star", data = data)

# The prevalence of misrepresentation;
(theta0 * p0) / (1 - theta0*(1-p0)) # 0.09677419

# Parameter estimates and estimated prevalence of
# misrepresentation (lambda);
summary(gamma_mod)

# Coefficients:
#           Estimate Std. Error   t value Pr(>|t|)
# (Intercept) 0.99356   0.03013 32.97245 <2e-16 ***
# X1          2.02152   0.03078 65.68276 <2e-16 ***
# X2b        -0.00679   0.03708 -0.18309  0.85477
# X2c        -1.02578   0.03684 -27.84599 <2e-16 ***
# X3          3.97883   0.01495 266.21973 <2e-16 ***
# V_star      2.00437   0.03107 64.51234 <2e-16 ***
# ---
# Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
# ---
#       AIC     AICc      BIC
# 5650.696 5650.841 5689.958
# ---
# Log-Likelihood
#      -2817.348
# ---
# Lambda:  0.1083894 std.err:  0.01160662

# Fitting an interaction between X2 and X3;

a6 <- -2
a7 <- 2

for(i in 1:n){

  if(X2[i] == "c"){
    mu[i] <- mu[i]*exp(a6*X3[i])
  }else{
    if(X2[i] == "b"){
      mu[i] <- mu[i]*exp(a7*X3[i])
    }
  }
}

```

```

        }
}

beta <- 1/mu/phi
Y <- rgamma(n, alpha0, beta)

data$Y <- Y

gamma_mod <- gammaRegMisrepEM(formula = Y ~ X1 + X2 + X3 + V_star + X2*X3,
                                v_star = "V_star", data = data)

summary(gamma_mod)

# Coefficients:
#               Estimate Std. Error   t value Pr(>|t|)
# (Intercept)  0.96205   0.03086 31.17145 <2e-16 ***
# X1          2.00411   0.03061 65.46734 <2e-16 ***
# X2b         -0.00987   0.03682 -0.26818  0.78862
# X2c         -0.99957   0.03733 -26.77449 <2e-16 ***
# X3          3.98282   0.02484 160.31083 <2e-16 ***
# V_star      2.01107   0.03077 65.36550 <2e-16 ***
# X2b:X3     1.95884   0.03573 54.82466 <2e-16 ***
# X2c:X3    -1.98595   0.03567 -55.67827 <2e-16 ***
# ---
# Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
# ---
#       AIC     AICc      BIC
# 5633.984 5634.207 5683.062
# ---
# Log-Likelihood
#      -2806.992
# ---
# Lambda: 0.1131951 std.err: 0.01181678

# Model fitting with a polynomial effect;

a8 <- -0.5

mu <- mu*exp(a8*X3^2)

beta <- 1/mu/phi
Y <- rgamma(n, alpha0, beta)

data$Y <- Y

gamma_mod <- gammaRegMisrepEM(formula = Y ~ X1 + X2 + X3 + V_star + X2*X3 + I(X3^2),
                                v_star = "V_star", data = data)

summary(gamma_mod)

# Coefficients:
#               Estimate Std. Error   t value Pr(>|t|)

```

```

# (Intercept) 1.04312   0.03164  32.96624 <2e-16 ***
# X1          2.04411   0.02929  69.79020 <2e-16 ***
# X2b         -0.10418   0.03512  -2.96620  0.00309  **
# X2c         -1.08910   0.03531  -30.84683 <2e-16 ***
# X3          4.00265   0.02421  165.31001 <2e-16 ***
# V_star      1.98741   0.02951  67.35719 <2e-16 ***
# I(X3^2)     -0.51152   0.01350  -37.90112 <2e-16 ***
# X2b:X3     1.98709   0.03598  55.22750 <2e-16 ***
# X2c:X3     -2.03395   0.03692  -55.09491 <2e-16 ***
# ---
# Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
# ---
#       AIC     AICc      BIC
# 4559.969 4560.236 4613.954
# ---
# Log-Likelihood
# -2268.984
# ---
# Lambda: 0.111464 std.err: 0.01173143

```

LnRegMisrepEM*Fit a Lognormal Misrepresentation Model using EM Algorithm***Description**

`LnRegMisrepEM` is used to fit a Lognormal regression model, adjusting for misrepresentation on a binary predictor. The function uses the Expectation Maximization algorithm and allows multiple additional correctly measured independent variables in the Lognormal regression with an identity link function that is typically used in insurance claims modeling. Standard errors of model estimates are obtained from closed form expressions of the Observed Fisher Information.

Usage

```
LnRegMisrepEM(formula, v_star, data, lambda = c(0.6,0.4),
              epsilon = 1e-08, maxit = 10000,
              maxrestarts = 20, verb = FALSE)
```

Arguments

- | | |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>formula</code> | an object of class " <code>formula</code> " (or one that can be coerced to that class): a symbolic description of the model to be fitted. The details of model specification are given under 'Details'. |
| <code>v_star</code> | a character specifying the name of the binary predictor that is suspected of being misrepresented. |
| <code>data</code> | a dataframe containing the variables in the model. |

lambda	initial mixing proportions used to start the EM algorithm. A numeric vector of length two, with the second element being the prevalence of misrepresentation.
epsilon	tolerance for convergence. Convergence is reached when the log-likelihood increases by less than epsilon.
maxit	the maximum number of iterations the EM routine will run for.
maxrestarts	how many times the EM routine will attempt to converge. When convergence is not achieved, the EM routine restarts with new randomly selected mixing proportions.
verb	logical. If TRUE, the difference in new .vs. old log-likelihood and the current log-likelihood is printed to the console after every iteration. If TRUE, the user will also be notified if the EM algorithm must restart with new mixing proportions.

Details

Please note: In the Log-Normal regression setting, the response is assumed to be Log-Normally distributed, so the function LnRegMisrepEM requires that the formula argument have a certain form: `log(response) ~ terms`. See 'Examples' for a demonstration.

Models for LnRegMisrepEM are specified symbolically. Like the `lm` and `glm` functions, the model has the form `response ~ terms`, where `response` is the numeric response vector and `terms` is a series of terms which specifies a linear predictor for `response`.

Currently, formula specification can accommodate the following expressions:

- transformations of the response: `log(y) ~ x`
- polynomial terms: `y ~ x + I(x^2)`
- interactions: `y ~ x*z`

Including an offset term (e.g. `y ~ x + offset()`) is currently not supported.

Value

`LnRegMisrepEM` returns an object of `class "misrepEM"`.

The function `summary` is used to obtain and print a summary of the results.

An object of class "`misrepEM`" is a list containing the following 14 elements:

y	the response used.
lambda	numeric. The estimated prevalence of misrepresentation.
params	a numeric vector containing the estimated parameters.
loglik	the final maximized log-likelihood.
posterior	a numeric vector. The posterior probability that the <i>i-th</i> observation is not misrepresented for observations where the suspected misrepresented variable is zero, based on the last iteration of the EM algorithm. The values are not meaningful for observations where the suspected misrepresented variable is one.
all.loglik	a numeric vector containing the log-likelihood at every iteration.

cov.estimates	the inverse of the observed fisher information matrix evaluated at the maximum likelihood estimates.
std.error	a numeric vector containing the standard errors of regression coefficients.
t.values	a numeric vector containing the standardized regression coefficients.
p.values	a numeric vector containing the <i>p</i> -values of the regression coefficients.
ICs	a numeric vector of length three containing the AIC, AICc, and BIC.
ft	a character containing the name of the function.
formula	an object of class formula indicating the model that was fit.
v_star_name	a character containing the name of the binary predictor suspected of misrepresentation.

References

- Xia, Michelle, Rexford Akakpo, and Matthew Albaugh. "Maximum Likelihood Approaches to Misrepresentation Models in GLM ratemaking: Model Comparisons." *Variance* 16.1 (2023).
- Akakpo, R. M., Xia, M., & Polansky, A. M. (2019). Frequentist inference in insurance ratemaking models adjusting for misrepresentation. *ASTIN Bulletin: The Journal of the IAA*, 49(1), 117-146.
- Xia, M., Hua, L., & Vadnais, G. (2018). Embedded predictive analysis of misrepresentation risk in GLM ratemaking models. *Variance*, 12(1), 39-58.

Examples

```
# Simulate data
n <- 1000
p0 <- 0.25

X1 <- rbinom(n, 1, 0.4)
X2 <- sample(x = c("a", "b", "c"), size = n, replace = TRUE)
X3 <- rnorm(n, 0, 1)

theta0 <- 0.3
V <- rbinom(n, 1, theta0)
V_star <- V
V_star[V==1] <- rbinom(sum(V==1), 1, 1-p0)

a0 <- 1
a1 <- 2
a2 <- 0
a3 <- -1
a4 <- 4
a5 <- 2

mu <- rep(0, n)

for(i in 1:n){
  mu[i] <- exp(a0 + a1*X1 + a4*X3 + a5*V )[i]
```

```

if(X2[i] == "a" || X2[i] == "b"){

  mu[i] <- mu[i]*exp(a2)

} else{
  mu[i] <- mu[i]*exp(a3)
}

sigma <- 0.427
mu.norm <- log(mu)-sigma^2/2
Y <- rlnorm(n, mu.norm, sigma)

data <- data.frame(Y = Y, X1 = X1, X2 = X2, X3 = X3, V_star = V_star)

# "a" is the reference
data$X2 <- as.factor(data$X2)

# Model with main effects:
LN_mod <- LnRegMisrepEM(formula = log(Y) ~ X1 + X2 + X3 + V_star,
                         v_star = "V_star", data = data)

# The prevalence of misrepresentation;
(theta0 * p0) / (1 - theta0*(1-p0)) # 0.09677419

# Parameter estimates and estimated prevalence of
# misrepresentation (lambda);
summary(LN_mod)

# Coefficients:
#             Estimate Std. Error   t value Pr(>|t|)
# (Intercept) 1.00664   0.02874 35.02082 <2e-16 ***
# X1          1.95903   0.02825 69.35263 <2e-16 ***
# X2b         0.04106   0.03413  1.20303  0.22925
# X2c        -1.00367   0.03418 -29.36328 <2e-16 ***
# X3          4.00031   0.01366 292.75312 <2e-16 ***
# V_star      2.01422   0.02922  68.93902 <2e-16 ***
# ---
# Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
# ---
#       AIC     AICc      BIC
# 5555.224 5555.370 5594.486
# ---
# Log-Likelihood
#      -2769.612
# ---
# Lambda:  0.11085 std.err:  0.01150365

# Fitting an interaction between X2 and X3;

a6 <- -2

```

```

a7 <- 2

for(i in 1:n){

  if(X2[i] == "c"){
    mu[i] <- mu[i]*exp(a6*X3[i])
  }else{
    if(X2[i] == "b"){
      mu[i] <- mu[i]*exp(a7*X3[i])
    }
  }
}

mu.norm <- log(mu)-sigma^2/2
Y <- rlnorm(n, mu.norm, sigma)

data$Y <- Y

LN_mod <- LnRegMisrepEM(formula = log(Y) ~ X1 + X2 + X3 + V_star + X2*X3,
                         v_star = "V_star", data = data)

summary(LN_mod)

# Coefficients:
#              Estimate Std. Error   t value Pr(>|t|)    
# (Intercept)  0.95064   0.02905 32.71943 <2e-16 ***
# X1          2.04258   0.02876 71.02228 <2e-16 ***  
# X2b         0.00204   0.03463  0.05879  0.95314  
# X2c        -0.97738   0.03469 -28.17315 <2e-16 ***  
# X3          3.97014   0.02341 169.61122 <2e-16 ***  
# V_star      2.01894   0.02967  68.04786 <2e-16 ***  
# X2b:X3     2.00436   0.03459  57.95433 <2e-16 ***  
# X2c:X3    -1.97573   0.03431 -57.59173 <2e-16 ***  
# ---      
# Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
# ---

#      AIC      AICc      BIC
# 5505.180 5505.402 5554.257
# ---

# Log-Likelihood
#           -2742.59
# ---

# Lambda: 0.1055629 std.err: 0.01134298

# Model fitting with a polynomial effect;

a8 <- -0.5

mu <- mu*exp(a8*X3^2)

mu.norm <- log(mu)-sigma^2/2
Y <- rlnorm(n, mu.norm, sigma)

```

```

data$Y <- Y

LN_mod <- LnRegMisrepEM(formula = log(Y) ~ X1 + X2 + X3 + V_star + X2*X3 + I(X3^2),
                         v_star = "V_star", data = data)

summary(LN_mod)

# Coefficients:
#               Estimate Std. Error   t value Pr(>|t|)
# (Intercept)  0.95591   0.03084 30.99533 <2e-16 ***
# X1          2.00070   0.02878 69.52672 <2e-16 ***
# X2b         0.09309   0.03480  2.67464  0.0076 **
# X2c        -0.96572   0.03455 -27.95530 <2e-16 ***
# X3          3.96765   0.02378 166.82860 <2e-16 ***
# V_star      2.00513   0.02967 67.58486 <2e-16 ***
# I(X3^2)    -0.49043   0.00983 -49.90063 <2e-16 ***
# X2b:X3     2.04614   0.03454  59.24411 <2e-16 ***
# X2c:X3    -1.97248   0.03383 -58.30378 <2e-16 ***
# ---
# Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
# ---
#       AIC     AICc      BIC
# 4537.485 4537.752 4591.470
# ---
# Log-Likelihood
#      -2257.742
# ---
# Lambda:  0.1061872 std.err:  0.01138758

```

Description

MEPS14 is a subset of the MEPS 2014 Full Year Consolidated Data File, as described in Xia et. al., (2023).

Usage

```
data("MEPS14")
```

Format

A data frame with 13,301 observations on the following 7 variables:

TOTEXP14 total medical expenditure.

OBTOTV14 total number of office-based visits.

UNINS14 uninsured status (1 - insured, 0 - uninsured).

SEX sex (1 - male, 0 - female).
 AGE14X age.
 ADSMOK42 smoking status (1 - yes, 0 - no).
 RTHLTH53 perceieved health status (1 - excellent, 5 - poor).

Source

https://meps.ahrq.gov/mepsweb/data_stats/download_data_files_detail.jsp?cboPufNumber=HC-171

References

Xia, Michelle, Rexford Akakpo, and Matthew Albaugh. "Maximum Likelihood Approaches to Misrepresentation Models in GLM ratemaking: Model Comparisons." *Variance* 16.1 (2023).

Examples

```
# Reproducing table 4 in Xia et. al., (2023).

data(MEPS14)

colMeans(MEPS14)
#    TOTEXP14      OBTOTV14      UNINS14          SEX      AGE14X      ADSMOK42      RTHLTH53
#5042.4647771    6.2260732    0.1242012    0.4153071   41.6628825   0.1670551    2.4319224

apply(MEPS14, 2, sd)
#    TOTEXP14      OBTOTV14      UNINS14          SEX      AGE14X      ADSMOK42      RTHLTH53
#1.358567e+04 1.272065e+01 3.298233e-01 4.927934e-01 1.332746e+01 3.730391e-01 1.074713e+00

sum(MEPS14$OBTOTV14 == 0) / nrow(MEPS14)
# [1] 0.1595369

sd(MEPS14$OBTOTV14 == 0)
# [1] 0.3661898

# Fit Gamma regression model with insured status as
# the misrepresented variable.
MEPS14$RTHLTH53 <- as.factor(MEPS14$RTHLTH53)

gamma_fit <- gammaRegMisrepEM(formula = TOTEXP14 ~ UNINS14
+ SEX + AGE14X + ADSMOK42 + RTHLTH53,
v_star = "UNINS14", data = MEPS14)

# summary returns a table of summary statistics, including
# goodness of fits (AIC, AICc, BIC), as well as the
# estimated prevalence of misrepresentation.
summary(gamma_fit)

# Coefficients:
#             Estimate Std. Error t value Pr(>|t|)
```

```

# (Intercept) 8.03379  0.05341 150.41937 <2e-16 ***
# UNINS14     -1.98132  0.03170 -62.49292 <2e-16 ***
# SEX          -0.20427  0.02669 -7.65320 <2e-16 ***
# AGE14X       0.02764  0.00099 27.83485 <2e-16 ***
# ADSMOK42    -0.08868  0.03653 -2.42776 0.01521   *
# RTHLTH532    0.24923  0.03533  7.05469 <2e-16 ***
# RTHLTH533    0.53860  0.03655 14.73488 <2e-16 ***
# RTHLTH534    1.00615  0.04837 20.80026 <2e-16 ***
# RTHLTH535    1.87845  0.08104 23.17833 <2e-16 ***
# ---
# Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
# ---
#      AIC      AICc      BIC
# 241083.9 241083.9 241166.3
# ---
# Log-Likelihood
#      -120530.9
# ---
# Lambda: 0.7734337 std.err: 0.009628053

# Fit Lognormal regression model with insured status as
# the misrepresented variable.
LN_fit <- LnRegMisrepEM(formula = log(TOTEXP14) ~ UNINS14
+ SEX + AGE14X + ADSMOK42 + RTHLTH53,
v_star = "UNINS14", data = MEPS14)

summary(LN_fit)

# Coefficients:
#              Estimate Std. Error t value Pr(>|t|)
# (Intercept) 7.28974  0.05648 129.05986 <2e-16 ***
# UNINS14     -1.29503  0.05496 -23.56317 <2e-16 ***
# SEX          -0.29590  0.02808 -10.53844 <2e-16 ***
# AGE14X       0.02460  0.00107 23.10180 <2e-16 ***
# ADSMOK42    -0.07008  0.03756 -1.86591 0.06208 .
# RTHLTH532    0.26349  0.03831  6.87786 <2e-16 ***
# RTHLTH533    0.47184  0.03942 11.97017 <2e-16 ***
# RTHLTH534    1.05065  0.04990 21.05580 <2e-16 ***
# RTHLTH535    1.94978  0.08067 24.16987 <2e-16 ***
# ---
# Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
# ---
#      AIC      AICc      BIC
# 239726.4 239726.4 239808.8
# ---
# Log-Likelihood
#      -119852.2
# ---
# Lambda: 0.1110631 std.err: 0.02548188

# Fit Negative Binomial regression model with insured status as

```

```

# the misrepresented variable.
NB_fit <- nbRegMisrepEM(formula = OBTOTV14 ~ UNINS14
+ SEX + AGE14X + ADSMOK42 + RTHLTH53,
v_star = "UNINS14", data = MEPS14)

summary(NB_fit)

# Coefficients:
#           Estimate Std. Error   t value Pr(>|t|)
# (Intercept) 2.00472   0.05463 36.69491 <2e-16 ***
# UNINS14    -1.68638   0.03371 -50.02640 <2e-16 ***
# SEX        -0.40917   0.02303 -17.76536 <2e-16 ***
# AGE14X      0.01897   0.00087 21.91823 <2e-16 ***
# ADSMOK42   -0.11391   0.03038 -3.74948 0.00018 ***
# RTHLTH532   0.20720   0.03183  6.50966 <2e-16 ***
# RTHLTH533   0.36794   0.03240 11.35678 <2e-16 ***
# RTHLTH534   0.72357   0.03978 18.18859 <2e-16 ***
# RTHLTH535   1.24468   0.06281 19.81714 <2e-16 ***
# ---
# Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
# ---
#       AIC     AICc      BIC
# 72788.71 72788.73 72871.16
# ---
# Log-Likelihood
#      -36383.35
# ---
# Lambda:  0.8351591 std.err:  0.009627158

# Fit Poisson regression model with smoking status as
# the misrepresented variable.
pois_fit <- poisRegMisrepEM(formula = OBTOTV14 ~ UNINS14
+ SEX + AGE14X + ADSMOK42 + RTHLTH53,
v_star = "UNINS14", data = MEPS14)

summary(pois_fit)

# Coefficients:
#           Estimate Std. Error   z value Pr(>|z|)
# (Intercept) 2.27367   0.02276 99.87676 <2e-16 ***
# UNINS14    -2.03719   0.00730 -279.00809 <2e-16 ***
# SEX        -0.18594   0.01090 -17.05204 <2e-16 ***
# AGE14X      0.01631   0.00042 38.90467 <2e-16 ***
# ADSMOK42   0.09594   0.01313  7.30930 <2e-16 ***
# RTHLTH532   0.14918   0.01641  9.09033 <2e-16 ***
# RTHLTH533   0.31282   0.01620 19.31078 <2e-16 ***
# RTHLTH534   0.75044   0.01793 41.85270 <2e-16 ***
# RTHLTH535   1.09859   0.02265 48.49410 <2e-16 ***
# ---
# Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
# ---

```

```
#      AIC     AICc      BIC
# 99599.31 99599.33 99674.27
# ---
# Log-Likelihood
#      -49789.66
# ---
# Lambda: 0.85957 std.err: 0.00348128
```

nbRegMisrepEM*Fit a Negative Binomial Misrepresentation Model using EM Algorithm***Description**

`nbRegMisrepEM` is used to fit a Negative Binomial regression model, adjusting for misrepresentation on a binary predictor. The function uses the Expectation Maximization algorithm and allows multiple additional correctly measured independent variables in the Negative Binomial regression with a log-link function that is typically used in insurance claims modeling. Standard errors of model estimates are obtained from closed form expressions of the Observed Fisher Information.

Usage

```
nbRegMisrepEM(formula, v_star, data, lambda = c(0.6, 0.4),
               epsilon = 1e-08, maxit = 10000,
               maxrestarts = 20, verb = FALSE)
```

Arguments

<code>formula</code>	an object of class " formula " (or one that can be coerced to that class): a symbolic description of the model to be fitted. The details of model specification are given under 'Details'.
<code>v_star</code>	a character specifying the name of the binary predictor that is suspected of being misrepresented.
<code>data</code>	a dataframe containing the variables in the model.
<code>lambda</code>	initial mixing proportions used to start the EM algorithm. A numeric vector of length two, with the second element being the prevalence of misrepresentation.
<code>epsilon</code>	tolerance for convergence. Convergence is reached when the log-likelihood increases by less than <code>epsilon</code> .
<code>maxit</code>	the maximum number of iterations the EM routine will run for.
<code>maxrestarts</code>	how many times the EM routine will attempt to converge. When convergence is not achieved, the EM routine restarts with new randomly selected mixing proportions.
<code>verb</code>	logical. If TRUE, the difference in new .vs. old log-likelihood and the current log-likelihood is printed to the console after every iteration. If TRUE, the user will also be notified if the EM algorithm must restart with new mixing proportions.

Details

Models for nbRegMisrepEM are specified symbolically. Like the `lm` and `glm` functions, the model has the form `response ~ terms`, where `response` is the numeric response vector and `terms` is a series of terms which specifies a linear predictor for `response`.

Currently, formula specification can accommodate the following expressions:

- transformations of the response: `log(y) ~ x`
- polynomial terms: `y ~ x + I(x^2)`
- interactions: `y ~ x*z`

Including an offset term (e.g. `y ~ x + offset()`) is currently not supported.

Value

`nbRegMisrepEM` returns an object of [class "misrepEM"](#).

The function `summary` is used to obtain and print a summary of the results.

An object of class "misrepEM" is a list containing the following 14 elements:

<code>y</code>	the response used.
<code>lambda</code>	numeric. The estimated prevalence of misrepresentation.
<code>params</code>	a numeric vector containing the estimated parameters.
<code>loglik</code>	the final maximized log-likelihood.
<code>posterior</code>	a numeric vector. The posterior probability that the <i>i-th</i> observation is not misrepresented for observations where the suspected misrepresented variable is zero, based on the last iteration of the EM algorithm. The values are not meaningful for observations where the suspected misrepresented variable is one.
<code>all.loglik</code>	a numeric vector containing the log-likelihood at every iteration.
<code>cov.estimates</code>	the inverse of the observed fisher information matrix evaluated at the maximum likelihood estimates.
<code>std.error</code>	a numeric vector containing the standard errors of regression coefficients.
<code>t.values</code>	a numeric vector containing the standardized regression coefficients.
<code>p.values</code>	a numeric vector containing the <i>p</i> -values of the regression coefficients.
<code>ICs</code>	a numeric vector of length three containing the AIC, AICc, and BIC.
<code>ft</code>	a character containing the name of the function.
<code>formula</code>	an object of class <code>formula</code> indicating the model that was fit.
<code>v_star_name</code>	a character containing the name of the binary predictor suspected of misrepresentation.

References

- Xia, Michelle, Rexford Akakpo, and Matthew Albaugh. "Maximum Likelihood Approaches to Misrepresentation Models in GLM ratemaking: Model Comparisons." *Variance* 16.1 (2023).
- Akakpo, R. M., Xia, M., & Polansky, A. M. (2019). Frequentist inference in insurance ratemaking models adjusting for misrepresentation. *ASTIN Bulletin: The Journal of the IAA*, 49(1), 117-146.
- Xia, M., Hua, L., & Vadnais, G. (2018). Embedded predictive analysis of misrepresentation risk in GLM ratemaking models. *Variance*, 12(1), 39-58.

Examples

```

set.seed(314159)

# Simulate data
n <- 1000
p0 <- 0.25

X1 <- rbinom(n, 1, 0.4)
X2 <- sample(x = c("a", "b", "c"), size = n, replace = TRUE)
X3 <- rnorm(n, 0, 1)

theta0 <- 0.3
V <- rbinom(n, 1, theta0)
V_star <- V
V_star[V==1] <- rbinom(sum(V==1), 1, 1-p0)

a0 <- 1
a1 <- 2
a2 <- 0
a3 <- -1
a4 <- 4
a5 <- 2

mu <- rep(0, n)

for(i in 1:n){

  mu[i] <- exp(a0 + a1*X1 + a4*X3 + a5*V )[i]

  if(X2[i] == "a" || X2[i] == "b"){

    mu[i] <- mu[i]*exp(a2)

  }else{
    mu[i] <- mu[i]*exp(a3)
  }

}

Y <- rnbinom(n, size = 1, mu = mu)

data <- data.frame(Y = Y, X1 = X1, X2 = X2, X3 = X3, V_star = V_star)

# "a" is the reference
data$X2 <- as.factor(data$X2)

# Model with main effects:
NB_mod <- nbRegMisrepEM(formula = Y ~ X1 + X2 + X3 + V_star,
                        v_star = "V_star", data = data)

# The prevalence of misrepresentation;

```

```

(theta0 * p0) / (1 - theta0*(1-p0)) # 0.09677419

# Parameter estimates and estimated prevalence of
# misrepresentation (lambda);
summary(NB_mod)

# Coefficients:
#             Estimate Std. Error t value Pr(>|t|)
# (Intercept) 0.94091   0.10797  8.71423 <2e-16 ***
# X1          2.03485   0.09517 21.38182 <2e-16 ***
# X2b         0.13346   0.10998  1.21356 0.22521
# X2c        -0.96514   0.11629 -8.29914 <2e-16 ***
# X3          4.07667   0.05874 69.40599 <2e-16 ***
# V_star      1.90011   0.09517 19.96485 <2e-16 ***
# ---
# Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
# ---
# AIC       AICc       BIC
# 7661.457 7661.602 7700.719
# ---
# Log-Likelihood
# -3822.728
# ---
# Lambda:  0.093119 std.err:  0.02233344

# Fitting an interaction between X2 and X3;

a6 <- -2
a7 <- 2

for(i in 1:n){

  if(X2[i] == "c"){
    mu[i] <- mu[i]*exp(a6*X3[i])
  }else{
    if(X2[i] == "b"){
      mu[i] <- mu[i]*exp(a7*X3[i])
    }
  }
}

Y <- rnbinom(n, size = 1, mu = mu)

data$Y <- Y

NB_mod <- nbRegMisrepEM(formula = Y ~ X1 + X2 + X3 + V_star + X2*X3,
                         v_star = "V_star", data = data)

summary(NB_mod)

# Coefficients:
#             Estimate Std. Error t value Pr(>|t|)

```

```

# (Intercept) 0.89452   0.11135   8.03331   <2e-16 ***
# X1          2.13269   0.08473   25.17143   <2e-16 ***
# X2b         -0.01559   0.12545   -0.12429   0.90111
# X2c         -0.95827   0.11665   -8.21469   <2e-16 ***
# X3          4.09454   0.09061   45.19049   <2e-16 ***
# V_star      2.08187   0.08503   24.48402   <2e-16 ***
# X2b:X3     1.84705   0.13130   14.06693   <2e-16 ***
# X2c:X3     -2.11044   0.11910   -17.72024   <2e-16 ***
# ---
# Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
# ---
#       AIC     AICc     BIC
# 7740.111 7740.334 7789.189
# ---
# Log-Likelihood
#      -3860.056
# ---
# Lambda:  0.08479587 std.err:  0.01901557

# Model fitting with a polynomial effect;

a8 <- -0.5

mu <- mu*exp(a8*X3^2)

Y <- rbinom(n, size = 1, mu = mu)

data$Y <- Y

NB_mod <- nbRegMisrepEM(formula = Y ~ X1 + X2 + X3 + V_star + X2*X3 + I(X3^2),
                         v_star = "V_star", data = data)

summary(NB_mod)

# Coefficients:
#             Estimate Std. Error t value Pr(>|t|)
# (Intercept) 0.96498   0.11201  8.61478   <2e-16 ***
# X1          2.09647   0.09310  22.51926   <2e-16 ***
# X2b         -0.02546   0.13341  -0.19082   0.8487
# X2c         -1.08524   0.12751  -8.51091   <2e-16 ***
# X3          4.03397   0.11939  33.78945   <2e-16 ***
# V_star      1.99765   0.09395  21.26217   <2e-16 ***
# I(X3^2)    -0.49023   0.05312  -9.22849   <2e-16 ***
# X2b:X3     2.00513   0.14127  14.19333   <2e-16 ***
# X2c:X3     -1.93432   0.13657  -14.16309   <2e-16 ***
# ---
# Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
# ---
#       AIC     AICc     BIC
# 7181.267 7181.535 7235.253
# ---
# Log-Likelihood

```

```
#      -3579.634
# ---
# Lambda: 0.1039235 std.err: 0.02154315
```

Description

NormRegMisrepEM is used to fit a Linear regression model, adjusting for misrepresentation on a binary predictor. The function uses the Expectation Maximization algorithm and allows multiple additional correctly measured independent variables in the Normal regression with an identity link function that is typically used in insurance claims modeling. Standard errors of model estimates are obtained from closed form expressions of the Observed Fisher Information.

Usage

```
NormRegMisrepEM(formula, v_star, data, lambda = c(0.6,0.4),
                 epsilon = 1e-08, maxit = 10000,
                 maxrestarts = 20, verb = FALSE)
```

Arguments

formula	an object of class " formula " (or one that can be coerced to that class): a symbolic description of the model to be fitted. The details of model specification are given under 'Details'.
v_star	a character specifying the name of the binary predictor that is suspected of being misrepresented.
data	a dataframe containing the variables in the model.
lambda	initial mixing proportions used to start the EM algorithm. A numeric vector of length two, with the second element being the prevalence of misrepresentation.
epsilon	tolerance for convergence. Convergence is reached when the log-likelihood increases by less than epsilon.
maxit	the maximum number of iterations the EM routine will run for.
maxrestarts	how many times the EM routine will attempt to converge. When convergence is not achieved, the EM routine restarts with new randomly selected mixing proportions.
verb	logical. If TRUE, the difference in new .vs. old log-likelihood and the current log-likelihood is printed to the console after every iteration. If TRUE, the user will also be notified if the EM algorithm must restart with new mixing proportions.

Details

Models for NormRegMisrepEM are specified symbolically. Like the `lm` and `glm` functions, the model has the form `response ~ terms`, where `response` is the numeric response vector and `terms` is a series of terms which specifies a linear predictor for `response`.

Currently, formula specification can accommodate the following expressions:

- transformations of the response: `log(y) ~ x`
- polynomial terms: `y ~ x + I(x^2)`
- interactions: `y ~ x*z`

Including an offset term (e.g. `y ~ x + offset()`) is currently not supported.

Value

`NormRegMisrepEM` returns an object of [class "misrepEM"](#).

The function `summary` is used to obtain and print a summary of the results.

An object of class "misrepEM" is a list containing the following 14 elements:

<code>y</code>	the response used.
<code>lambda</code>	numeric. The estimated prevalence of misrepresentation.
<code>params</code>	a numeric vector containing the estimated parameters.
<code>loglik</code>	the final maximized log-likelihood.
<code>posterior</code>	a numeric vector. The posterior probability that the i -th observation is not misrepresented for observations where the suspected misrepresented variable is zero, based on the last iteration of the EM algorithm. The values are not meaningful for observations where the suspected misrepresented variable is one.
<code>all.loglik</code>	a numeric vector containing the log-likelihood at every iteration.
<code>cov.estimates</code>	the inverse of the observed fisher information matrix evaluated at the maximum likelihood estimates.
<code>std.error</code>	a numeric vector containing the standard errors of regression coefficients.
<code>t.values</code>	a numeric vector containing the standardized regression coefficients.
<code>p.values</code>	a numeric vector containing the p -values of the regression coefficients.
<code>ICs</code>	a numeric vector of length three containing the AIC, AICc, and BIC.
<code>ft</code>	a character containing the name of the function.
<code>formula</code>	an object of class <code>formula</code> indicating the model that was fit.
<code>v_star_name</code>	a character containing the name of the binary predictor suspected of misrepresentation.

References

- Xia, Michelle, Rexford Akakpo, and Matthew Albaugh. "Maximum Likelihood Approaches to Misrepresentation Models in GLM ratemaking: Model Comparisons." *Variance* 16.1 (2023).
- Akakpo, R. M., Xia, M., & Polansky, A. M. (2019). Frequentist inference in insurance ratemaking models adjusting for misrepresentation. *ASTIN Bulletin: The Journal of the IAA*, 49(1), 117-146.
- Xia, M., Hua, L., & Vadnais, G. (2018). Embedded predictive analysis of misrepresentation risk in GLM ratemaking models. *Variance*, 12(1), 39-58.

Examples

```

# Simulate data
n <- 1000
p0 <- 0.25

X1 <- rbinom(n, 1, 0.4)
X2 <- sample(x = c("a", "b", "c"), size = n, replace = TRUE)
X3 <- rnorm(n, 0, 1)

theta0 <- 0.3
V <- rbinom(n, 1, theta0)
V_star <- V
V_star[V==1] <- rbinom(sum(V==1), 1, 1-p0)

a0 <- 1
a1 <- 2
a2 <- 0
a3 <- -1
a4 <- 4
a5 <- 2

mu <- rep(0, n)

for(i in 1:n){

  mu[i] <- (a0 + a1*X1 + a4*X3 + a5*V )[i]

  if(X2[i] == "a" || X2[i] == "b"){

    mu[i] <- mu[i] + a2

  }else{
    mu[i] <- mu[i] + a3
  }

}

sigma <- 0.427

Y <- rnorm(n, mu, sigma)

data <- data.frame(Y = Y, X1 = X1, X2 = X2, X3 = X3, V_star = V_star)

# "a" is the reference
data$X2 <- as.factor(data$X2)

# Model with main effects:
norm_lm <- NormRegMisrepEM(formula = Y ~ X1 + X2 + X3 + V_star,
                             v_star = "V_star", data = data)

# The prevalence of misrepresentation;
(theta0 * p0) / (1 - theta0*(1-p0)) # 0.09677419

```

```

# Parameter estimates and estimated prevalence of
# misrepresentation (lambda);
summary(norm_lm)

# Coefficients:
#             Estimate Std. Error   t value Pr(>|t|)
# (Intercept) 1.00624   0.02834 35.50820 <2e-16 ***
# X1          1.95903   0.02825 69.35263 <2e-16 ***
# X2b         0.04106   0.03413  1.20301 0.22926
# X2c        -1.00367   0.03418 -29.36328 <2e-16 ***
# X3          4.00031   0.01366 292.75308 <2e-16 ***
# V_star      2.01422   0.02922 68.93901 <2e-16 ***
# ---
# Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
# ---
#       AIC     AICc      BIC
# 1674.683 1674.828 1713.945
# ---
# Log-Likelihood
#      -829.3415
# ---
# Lambda:  0.11085 std.err:  0.01150365

# Fitting an interaction between X2 and X3;

a6 <- -2
a7 <- 2

for(i in 1:n){

  if(X2[i] == "c"){
    mu[i] <- mu[i] + a6*X3[i]
  }else{
    if(X2[i] == "b"){
      mu[i] <- mu[i] + a7*X3[i]
    }
  }
}

Y <- rnorm(n, mu, sigma)

data$Y <- Y

norm_lm <- NormRegMisrepEM(formula = Y ~ X1 + X2 + X3 + V_star + X2*X3,
                           v_star = "V_star", data = data)

summary(norm_lm)

# Coefficients:
#             Estimate Std. Error   t value Pr(>|t|)
# (Intercept) 0.94905   0.02866 33.11281 <2e-16 ***
# X1          2.04258   0.02876 71.02223 <2e-16 ***

```

```

# X2b      0.00204  0.03463  0.05880  0.95313
# X2c     -0.97738  0.03469 -28.17313 <2e-16 ***
# X3       3.97014  0.02341 169.61108 <2e-16 ***
# V_star    2.01894  0.02967  68.04780 <2e-16 ***
# X2b:X3   2.00436  0.03459  57.95430 <2e-16 ***
# X2c:X3  -1.97573  0.03431 -57.59168 <2e-16 ***
# ---
# Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
# ---
#      AIC      AICc      BIC
# 1668.925 1669.148 1718.003
# ---
# Log-Likelihood
#      -824.4626
# ---
# Lambda:  0.1055629 std.err:  0.01134299

# Model fitting with a polynomial effect;

a8 <- -0.5

mu <- mu + a8*X3^2

Y <- rnorm(n, mu, sigma)

data$Y <- Y

norm_lm <- NormRegMisrepEM(formula = Y ~ X1 + X2 + X3 + V_star + X2*X3 + I(X3^2),
                             v_star = "V_star", data = data)

summary(norm_lm)

# Coefficients:
#             Estimate Std. Error t value Pr(>|t|)
# (Intercept) 0.95426  0.03050 31.28435 <2e-16 ***
# X1          2.00070  0.02878 69.52668 <2e-16 ***
# X2b         0.09309  0.03480  2.67463  0.0076 **
# X2c        -0.96572  0.03455 -27.95529 <2e-16 ***
# X3          3.96765  0.02378 166.82865 <2e-16 ***
# V_star      2.00513  0.02967  67.58481 <2e-16 ***
# I(X3^2)    -0.49043  0.00983 -49.90057 <2e-16 ***
# X2b:X3    2.04613  0.03454  59.24406 <2e-16 ***
# X2c:X3  -1.97248  0.03383 -58.30381 <2e-16 ***
# ---
# Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
# ---
#      AIC      AICc      BIC
# 1672.933 1673.200 1726.918
# ---
# Log-Likelihood
#      -825.4665
# ---
# Lambda:  0.1061873 std.err:  0.01138759

```

poisRegMisrepEM*Fit a Poisson Misrepresentation Model using EM Algorithm*

Description

`poisRegMisrepEM` is used to fit a Poisson regression model, adjusting for misrepresentation on a binary predictor. The function uses the Expectation Maximization algorithm and allows multiple additional correctly measured independent variables in the Poisson regression with a log-link function that is typically used in insurance claims modeling. Standard errors of model estimates are obtained from closed form expressions of the Observed Fisher Information.

Usage

```
poisRegMisrepEM(formula, v_star, data, lambda = c(0.6,0.4),
                 epsilon = 1e-08, maxit = 10000,
                 maxrestarts = 20, verb = FALSE)
```

Arguments

<code>formula</code>	an object of class " formula " (or one that can be coerced to that class): a symbolic description of the model to be fitted. The details of model specification are given under 'Details'.
<code>v_star</code>	a character specifying the name of the binary predictor that is suspected of being misrepresented.
<code>data</code>	a dataframe containing the variables in the model.
<code>lambda</code>	initial mixing proportions used to start the EM algorithm. A numeric vector of length two, with the second element being the prevalence of misrepresentation.
<code>epsilon</code>	tolerance for convergence. Convergence is reached when the log-likelihood increases by less than <code>epsilon</code> .
<code>maxit</code>	the maximum number of iterations the EM routine will run for.
<code>maxrestarts</code>	how many times the EM routine will attempt to converge. When convergence is not achieved, the EM routine restarts with new randomly selected mixing proportions.
<code>verb</code>	logical. If TRUE, the difference in new .vs. old log-likelihood and the current log-likelihood is printed to the console after every iteration. If TRUE, the user will also be notified if the EM algorithm must restart with new mixing proportions.

Details

Models for `poisRegMisrepEM` are specified symbolically. Like the `lm` and `glm` functions, the model has the form `response ~ terms`, where `response` is the numeric response vector and `terms` is a series of terms which specifies a linear predictor for `response`.

Currently, formula specification can accommodate the following expressions:

- transformations of the response: `log(y) ~ x`
- polynomial terms: `y ~ x + I(x^2)`
- interactions: `y ~ x*z`

Including an offset term (e.g. `y ~ x + offset()`) is currently not supported.

Value

`poisRegMisrepEM` returns an object of `class "misrepEM"`.

The function `summary` is used to obtain and print a summary of the results.

An object of class `"misrepEM"` is a list containing the following 14 elements:

<code>y</code>	the response used.
<code>lambda</code>	numeric. The estimated prevalence of misrepresentation.
<code>params</code>	a numeric vector containing the estimated parameters.
<code>loglik</code>	the final maximized log-likelihood.
<code>posterior</code>	a numeric vector. The posterior probability that the i -th observation is not misrepresented for observations where the suspected misrepresented variable is zero, based on the last iteration of the EM algorithm. The values are not meaningful for observations where the suspected misrepresented variable is one.
<code>all.loglik</code>	a numeric vector containing the log-likelihood at every iteration.
<code>cov.estimates</code>	the inverse of the observed fisher information matrix evaluated at the maximum likelihood estimates.
<code>std.error</code>	a numeric vector containing the standard errors of regression coefficients.
<code>z.values</code>	a numeric vector containing the standardized regression coefficients.
<code>p.values</code>	a numeric vector containing the p -values of the regression coefficients.
<code>ICs</code>	a numeric vector of length three containing the AIC, AICc, and BIC.
<code>ft</code>	a character containing the name of the function.
<code>formula</code>	an object of class <code>formula</code> indicating the model that was fit.
<code>v_star_name</code>	a character containing the name of the binary predictor suspected of misrepresentation.

References

- Xia, Michelle, Rexford Akakpo, and Matthew Albaugh. "Maximum Likelihood Approaches to Misrepresentation Models in GLM ratemaking: Model Comparisons." *Variance* 16.1 (2023).
- Akakpo, R. M., Xia, M., & Polansky, A. M. (2019). Frequentist inference in insurance ratemaking models adjusting for misrepresentation. *ASTIN Bulletin: The Journal of the IAA*, 49(1), 117-146.
- Xia, M., Hua, L., & Vadnais, G. (2018). Embedded predictive analysis of misrepresentation risk in GLM ratemaking models. *Variance*, 12(1), 39-58.

Examples

```

set.seed(314159)

# Simulate data
n <- 1000
p0 <- 0.25

X1 <- rbinom(n, 1, 0.4)
X2 <- sample(x = c("a", "b", "c"), size = n, replace = TRUE)
X3 <- rnorm(n, 0, 1)

theta0 <- 0.3
V <- rbinom(n, 1, theta0)
V_star <- V
V_star[V==1] <- rbinom(sum(V==1), 1, 1-p0)

a0 <- 1
a1 <- 0.5
a2 <- 0
a3 <- -1
a4 <- 2
a5 <- 1

mu <- rep(0, n)

for(i in 1:n){

  mu[i] <- exp(a0 + a1*X1 + a4*X3 + a5*V )[i]

  if(X2[i] == "a" || X2[i] == "b"){

    mu[i] <- mu[i]*exp(a2)

  }else{
    mu[i] <- mu[i]*exp(a3)
  }

}

Y <- rpois(n, mu)

data <- data.frame(Y = Y, X1 = X1, X2 = X2, X3 = X3, V_star = V_star)

# "a" is the reference
data$X2 <- as.factor(data$X2)

# Model with main effects:
pois_mod <- poisRegMisrepEM(formula = Y ~ X1 + X2 + X3 + V_star,
                             v_star = "V_star", data = data)

# The prevalence of misrepresentation;

```

```

(theta0 * p0) / (1 - theta0*(1-p0)) # 0.09677419

# Parameter estimates and estimated prevalence of
# misrepresentation (lambda);
summary(pois_mod)

# Coefficients:
#             Estimate Std. Error   z value Pr(>|z|)
# (Intercept) 1.03519   0.02238 46.25615 <2e-16 ***
# X1          0.49875   0.01297 38.45157 <2e-16 ***
# X2b        -0.00007   0.01324 -0.00500  0.99601
# X2c        -0.98438   0.01926 -51.10084 <2e-16 ***
# X3          1.97794   0.00878 225.20267 <2e-16 ***
# V_star      0.99484   0.01290 77.14885 <2e-16 ***
# ---
# Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
# ---
# AIC       AICc       BIC
# 4170.836  4170.949  4205.190
# ---
# Log-Likelihood
# -2078.418
# ---
# Lambda:  0.1039615 std.err:  0.01613403

# Fitting an interaction between X2 and X3;

a6 <- -0.5
a7 <- -0.5

for(i in 1:n){

  if(X2[i] == "c"){
    mu[i] <- mu[i]*exp(a6*X3[i])
  }else{
    if(X2[i] == "b"){
      mu[i] <- mu[i]*exp(a7*X3[i])
    }
  }
}

Y <- rpois(n, mu)

data$Y <- Y

pois_mod <- poisRegMisrepEM(formula = Y ~ X1 + X2 + X3 + V_star + X2*X3,
                             v_star = "V_star", data = data)

summary(pois_mod)

# Coefficients:
#             Estimate Std. Error   z value Pr(>|z|)
# (Intercept) 0.98723   0.02917 33.84255 <2e-16 ***

```

```

# X1          0.50135   0.01540  32.56094 <2e-16 ***
# X2b        -0.03643   0.03655  -0.99648  0.31902
# X2c        -1.02315   0.05170  -19.79103 <2e-16 ***
# X3          1.99527   0.01319  151.22592 <2e-16 ***
# V_star      1.00917   0.01531   65.93335 <2e-16 ***
# X2b:X3     -0.47260   0.02137  -22.11569 <2e-16 ***
# X2c:X3     -0.49639   0.03018  -16.44530 <2e-16 ***
# ---
# Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
# ---
#      AIC      AICc      BIC
# 4096.533 4096.714 4140.702
# ---
# Log-Likelihood
#      -2039.266
# ---
# Lambda:  0.1072814 std.err:  0.0162925

# Model fitting with a polynomial effect;

a8 <- -1

mu <- mu*exp(a8*X3^2)

Y <- rpois(n, mu)

data$Y <- Y

pois_mod <- poisRegMisrepEM(formula = Y ~ X1 + X2 + X3 + V_star + X2*X3 + I(X3^2),
                             v_star = "V_star", data = data)

summary(pois_mod)

# Coefficients:
#             Estimate Std. Error   z value Pr(>|z|)
# (Intercept) 1.03291   0.04647 22.22701 <2e-16 ***
# X1          0.43783   0.03453 12.68058 <2e-16 ***
# X2b        -0.08042   0.05600 -1.43609  0.15098
# X2c        -1.02676   0.07523 -13.64912 <2e-16 ***
# X3          2.03183   0.06317 32.16597 <2e-16 ***
# V_star      0.98563   0.03415 28.86175 <2e-16 ***
# I(X3^2)    -0.99795   0.03529 -28.27715 <2e-16 ***
# X2b:X3     -0.45828   0.06499 -7.05189 <2e-16 ***
# X2c:X3     -0.47648   0.08912 -5.34623 <2e-16 ***
# ---
# Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
# ---
#      AIC      AICc      BIC
# 3269.698 3269.920 3318.775
# ---
# Log-Likelihood
#      -1624.849
# ---

```

```
# Lambda: 0.108672 std.err: 0.02181499
```

predict.misrepEM *Predict method for 'misrepEM' Model Fits*

Description

Predicted values based on a fitted 'misrepEM' model object.

Usage

```
## S3 method for class 'misrepEM'  
predict(object, newdata, ...)
```

Arguments

- object a fit from one of gammaRegMisrepEM, LnRegMisrepEM, NormRegMisrepEM, nbRegMisrepEM, or poisRegMisrepEM.
- newdata a data frame containing predictors that are to be used to make predictions of the response.
- ... currently not used.

Details

Currently, only predictions made on the scale of the response variable are supported.

Incomplete cases are automatically dropped, and predictions are made only on complete cases.

Value

`predict.misrepEM` returns a numeric vector of predictions.

References

- Xia, Michelle, Rexford Akakpo, and Matthew Albaugh. "Maximum Likelihood Approaches to Misrepresentation Models in GLM ratemaking: Model Comparisons." *Variance* 16.1 (2023).
- Akakpo, R. M., Xia, M., & Polansky, A. M. (2019). Frequentist inference in insurance ratemaking models adjusting for misrepresentation. *ASTIN Bulletin: The Journal of the IAA*, 49(1), 117-146.
- Xia, M., Hua, L., & Vadnais, G. (2018). Embedded predictive analysis of misrepresentation risk in GLM ratemaking models. *Variance*, 12(1), 39-58.

Examples

```

# Simulate data
n <- 2000
p0 <- 0.25

X1 <- rbinom(n, 1, 0.4)
X2 <- rnorm(n, 0, 1)
X3 <- rbeta(n, 2, 1)

theta0 <- 0.3
V <- rbinom(n,1,theta0)
V_star <- V
V_star[V==1] <- rbinom(sum(V==1),1,1-p0)

a0 <- 1
a1 <- 2
a2 <- 0
a3 <- 4
a4 <- 2

mu <- exp(a0 + a1*X1 + a2*X2 + a3*X3 + a4*V)

phi <- 0.2
alpha0 <- 1/phi
beta <- 1/mu/phi
Y <- rgamma(n, alpha0, beta)

data <- data.frame(Y = Y, X1 = X1, X2 = X2, X3 = X3, V_star = V_star)

# Split data into training and testing sets
train <- data[1:1800,]
test <- data[1801:2000,]

gamma_fit <- gammaRegMisrepEM(formula = Y ~ X1 + X2 + X3 + V_star,
                               v_star = "V_star", data = train)

# Predict on test set;
preds <- predict(gamma_fit, newdata = test)

```

summary.misrepEM

Summarize a 'misrepEM' Model Fit

Description

summary method for class 'misrepEM'.

Usage

```
## S3 method for class 'misrepEM'
summary(object, ...)

## S3 method for class 'summary.misrepEM'
print(x, ...)
```

Arguments

object	an object of class "misrepEM", usually resulting from a call to one of <code>gammaRegMisrepEM</code> , <code>LnRegMisrepEM</code> , <code>NormRegMisrepEM</code> , <code>nbRegMisrepEM</code> or <code>poisRegMisrepEM</code> .
x	an object of class "summary.misrepEM", usually resulting from a call to <code>summary.misrepEM</code> .
...	currently not used.

Value

`summary.misrepEM` returns an object of class "summary.misrepEM", a list of length 5 with the following components:

coefficients	a data.frame of coefficients, standard errors, standardized coefficients, two-tailed p-values corresponding to the standardized coefficient based on a Student-t or Normal reference distribution, and 'significance stars.'
ICs	a named numeric vector of length three, containing the Akaike Information Criterion (AIC), the corrected AIC (AICc) and the Bayesian Information Criterion (BIC).
loglik	numeric. The log-likelihood of the fitted misrepEM model.
lambda	numeric. The estimated prevalence of misrepresentation.
lambda_stderro	numeric. The standard error of the estimated prevalence of misrepresentation.

References

- Xia, Michelle, Rexford Akakpo, and Matthew Albaugh. "Maximum Likelihood Approaches to Misrepresentation Models in GLM ratemaking: Model Comparisons." *Variance* 16.1 (2023).
- Akakpo, R. M., Xia, M., & Polansky, A. M. (2019). Frequentist inference in insurance ratemaking models adjusting for misrepresentation. *ASTIN Bulletin: The Journal of the IAA*, 49(1), 117-146.
- Xia, M., Hua, L., & Vadnais, G. (2018). Embedded predictive analysis of misrepresentation risk in GLM ratemaking models. *Variance*, 12(1), 39-58.

Examples

```
# Simulate data
n <- 2000
p0 <- 0.25

X1 <- rbinom(n, 1, 0.4)
X2 <- rnorm(n, 0, 1)
```

```

X3 <- rbeta(n, 2, 1)

theta0 <- 0.3
V <- rbinom(n,1,theta0)
V_star <- V
V_star[V==1] <- rbinom(sum(V==1),1,1-p0)

a0 <- 1
a1 <- 2
a2 <- 0
a3 <- 4
a4 <- 2

mu <- exp(a0 + a1*X1 + a2*X2 + a3*X3 + a4*V)

phi <- 0.2
alpha0 <- 1/phi
beta <- 1/mu/phi
Y <- rgamma(n, alpha0, beta)

data <- data.frame(Y = Y, X1 = X1, X2 = X2, X3 = X3, V_star = V_star)

gamma_fit <- gammaRegMisrepEM(formula = Y ~ X1 + X2 + X3 + V_star,
                               v_star = "V_star", data = data)

summary(gamma_fit)

# Coefficients:
#              Estimate Std. Error t value Pr(>|t|)
# (Intercept) 1.00137   0.03413 29.33857 <2e-16 ***
# X1          2.01388   0.02154 93.48440 <2e-16 ***
# X2         -0.00193   0.01038 -0.18589  0.85255
# X3          4.00101   0.04560 87.74528 <2e-16 ***
# V_star      2.00567   0.02240 89.54515 <2e-16 ***
# ---
# Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
# ---
# AIC       AICc       BIC
# 23362.50 23362.56 23401.71
# ---
# Log-Likelihood
# -11674.25
# ---
# Lambda: 0.09635239 std.err: 0.007641834

```

Index

* **datasets**
MEPS14, 12

class, 3, 8, 17, 22, 27

formula, 2, 7, 16, 21, 26

gammaRegMisrepEM, 2, 33

LnRegMisrepEM, 7, 33

MEPS14, 12

nbRegMisrepEM, 16, 33
NormRegMisrepEM, 21, 33

poisRegMisrepEM, 26, 33
predict.misrepEM, 31
print.summary.misrepEM
 (summary.misrepEM), 32

summary.misrepEM, 32